VIKING[™] 1740 Series



KEY FEATURES

Quality

- Perfect 1/1/1/1 Optical Clarity
- 1/25,000 sec. Switching Time (Inactive to Active)
- · 2 Year Warranty

Control

- Variable 9-13 Shade, Sensitivity & Delay Control
- Weld & Grind Mode
- · User Replaceable AAA Batteries

Safety

- · ANSI Z87.1-2010 & CSA Z94.3 Compliant
- · Auto On / Off Functionality
- Test Mechanism & LED Low Battery Indicator

Process »

Stick, TIG, Pulsed TIG, MIG, Pulsed MIG, Flux-Cored, Gouging, Grinding







Optical Clarity - Why It's Important

Optical Clarity

The NEW VIKING™ 1740 Series auto-darkening helmets have a perfect EN379 - 1/1/1/1 optical clarity rating. This test measures the performance of the auto-darkening filter on four separate optical categories.

Each Category is graded on a scale of 1-3, with a score of 1 being the best and 3 being the worst.

Categories

- 1. Optical Class Distortion
- 2. Diffusion of Light Class Blurriness
- **3. Variations of Luminous Transmittance** Shade Consistency & Accuracy
- 4. Angle Dependence of Luminous Transmittance Class Shade Consistency & Accuracy at an Angle



Perfect Lincoln Electric rating of 1/1/1/1

NOTE: The illustration above represents the improved clarity possible with the latest VIKING helmets. Visit your local Lincoln Electric distributor to view the upgraded VIKING clarity under actual welding conditions.

VIKING™ 1740 Series Helmets



VIKING[™] 1740 BLACK K3282-2



VIKING[™] 1740 ReCode[™] K3495-2



VIKING[™] 1740 Ignition[™] K4375-2

REPLACEMENT PARTS

Sales Number	Description	Dimensions	Package Qty.	
KP3284-2	1740 ADF CARTRIDGE	STD 110 x 90	1	
KP3283-1	1740 INSIDE CLEAR COVER LENS KIT	95.9 x 47.2 x 1.00 mm	2	
KP2930-1	SWEATBAND	N/A	2	
KP4100-1	HEADGEAR W/SWEATBAND	N/A	1	
KP3047-1	HARD HAT ADAPTER	N/A	1	
S27978-58	OUTSIDE COVER LENS SEAL	N/A	1	
S27978-55	ADF HOLDER	N/A	1	
KP 3043-1	OUTSIDE COVER LENS	114 x 100 x 1.5 mm	5	
S27978-95	1740 BLACK REPLACEMENT SHELL	N/A	1	

Product Specifications

Product Name	Lens Switching Speed (sec)	Variable Shade/ Control	Magnifying "Cheater" Lens Capable	Grind Mode	Light Sensitivity Control		Delay Control Dark to Light (sec)	TIG Amp Rating	Cartridge Size in. (mm)	View Size in. (mm)	Temperature Range	Weight oz. (g)	Warranty
VIKING™ 1740 Series Helmets	1/25,000	9-13/ Internal	Yes	DIN 4	Variable	2	0.10-1.0 Adjustable	≥ 5 Amp AC/DC	4.33 x 3.54 (110 x 90)	3.78 x 1.67 (96 x 42.5)	Operating -10°C - 55°C (14°F - 131°F) Storage -20°C - 70°C (-4°F - 158°F)	18.6 (528)	2 years

CUSTOMER ASSISTANCE POLICY

The business of The Lincoln Electric Company is manufacturing and selling high quality welding equipment, consumables, and cutting equipment. Our challenge is to meet the needs of our customers and to exceed their expectations. On occasion, purchasers may ask Lincoln Electric for information or advice about their use of our products. Our employees respond to inquiries to the best of their ability based on information provided to them by the customers and the knowledge they may have concerning the application. Our employees, however, are not in a position to verify the information provided or to evaluate the engineering requirements for the particular weldment. Accordingly, Lincoln Electric does not verant or guarantee or assume any liability with respect to such information or advice. Moreover, the provision of such information or advice does not create, expand, or alter any warranty on our products. Any express or implied warranty that might arise from the information or advice, including any implied warranty of merchantalitify or any warranty of interess for any customers' particular purpose is specifically disclaimed.

Lincoln Electric is a responsive manufacturer, but the selection and use of specific products sold by Lincoln Electric is solely within the control of, and remains the sole responsibility of the customer. Many variables beyond the control of Lincoln Electric affect the results obtained in applying these types of fabrication methods and service requirements.

Subject to Change – This information is accurate to the best of our knowledge at the time of printing. Please refer to www.lincolnelectric.com for any updated information.